



# WONDER-PRIME™

## MULTI-PURPOSE INTERIOR ACRYLIC LATEX PRIMER-SEALER DR 51701

Read Label and Material Safety Data Sheet prior to use. See cautions on last page.

### D E S C R I P T I O N

A premium quality all purpose latex primer-sealer for use under wallcovering, or under alkyd or latex wall paints or enamels. Bonds to clean glossy, hard surfaces such as aged oil base or alkyd enamels without sanding. One coat prepares surfaces for painting or wall covering. Can be used on wood, drywall, plaster, masonry or hardboard. Features easy application, quick dry, good sanding, excellent sealing, alkali resistance. Particularly good in high moisture areas such as kitchens and

bathrooms. Ideal for use as a primer-sealer for drywall prior to hanging all types of wallcovering. Hides taped areas, spackled spots and color differences on the wall so they won't show through wallcovering. Aids future removal of wallcovering. This product is a vapor barrier (<1.0 perm) when applied at a minimum of 6 wet mils as tested under ASTM D96.

### F E A T U R E S

- One coat prepares surfaces for painting or wallcovering
- Bonds to glossy surfaces without sanding
- Excellent enamel holdout and sealing
- Moisture and alkali resistant
- Fast dry and recoat
- Quick sanding
- Enhances wallcovering adhesion
- Aid future strippability of wallcovering
- Low odor
- Devoe performance alternate for Federal Specification TT-P-650D
- Low VOC

### C O M P O S I T I O N

- Advanced Devcryn Latex Technology
- Titanium Dioxide and Extender Pigments
- Not formulated with lead or mercury containing materials.

### S P E C I F I C A T I O N D A T A

**Colors:** White; tintable

**Finish:** Flat

**Clean-up Solvent:** Soap and Water

**Density:** 11.1 lbs./gal. (1.33 kg/L)

**VOC:** 0.90 lbs./gal. (108 g/L)

**Flame Spread Rating:** Class A (0-25) on non-combustible surfaces

**Solids:** Volume - 31% ± 1%

Weight - 48% ± 1%

**Practical Coverage:** Apply at 350-400 sq. ft. per gallon (9-10 m<sup>2</sup>/L) depending on surface texture and porosity.

**Flash Point:** Non-flammable

**Dry Time @ 77°F (25°C) & 50% RH:**

To touch: 1/2 hour

To recoat: 4 hours

**To Wallcover:** Allow 2 hours dry time (24 hours if adhesive is rolled on wall)

**Shelf Life:** Over 1 year

## S U R F A C E P R E P A R A T I O N

All surfaces must be sound, dry, clean and free of oil, grease, wax, polish, mildew, form release agents, curing compounds and foreign matter. Remove all loose paint, rust and scale by scraping and wire brushing. Scuff sanding is required only on glossy hard, slick or dense surfaces which are subject to high levels of moisture.

**NEW SURFACES: DRYWALL** - Prime with this paint. When this primer and a latex or alkyd finish are spray-applied, it is necessary to back-roll this primer and the first topcoat immediately after spraying. This will prevent pin-holing. **CONCRETE, MASONRY AND PLASTER** - Cure at least 30 days before painting. pH must be 10.0 or lower. Roughen slick poured or precast concrete by acid etching or sandsweeping. Follow acid manufacturer's application and safety instructions. Rinse thoroughly with water and allow to dry. Remove loose aggregate.

Lightly dampen surface to ease application in hot, dry weather. Fill block with Devoe latex block filler DV 52903. Prime with This paint. **WOOD** - Set nails. Fill nail holes and cracks with latex spackle. Prime with this paint. **METAL** - Clean and prime with Devoe waterborne metal primer DP 85XX or solventborne primer DP 13201.

**PREVIOUSLY PAINTED SURFACES:** Remove oil or grease residue by washing. Rinse thoroughly with water and allow to dry. Sanding is not required if the surface is properly and thoroughly cleaned (scuff sanding is required only on glossy, hard, slick or dense surfaces which are subject to high levels of moisture). Remove loose paint. Fill cracks with latex-type filler. Prime any bare areas with this product.

## D I R E C T I O N S

**TINTING:** May be tinted toward the finish color with up to two oz. of ICI Colorants per gallon. When used as a wallcovering primer-sealer, tinting toward the wallcovering background color will help avoid visible seams.

**SPREADING RATE:** Apply at 350-400 sq. ft. per gallon (9-10 m<sup>2</sup>/L) depending on surface texture and porosity. Two coats may be necessary on rough or porous surfaces to achieve proper film thickness.

**APPLICATION:** Brush, short nap roller or spray. No thinning required. For airless spray use a .015" tip. Adjust pressure as needed. Do not apply when surface or air temperature is below 50°F (10°C). Provide good ventilation and warmth for normal drying.

**DRYING TIME:** At 77°F (25°C) and 50% R.H., dries to touch in one-half hour and to sand or recoat or apply wallcovering over in two hours (in cool, damp weather or poorly ventilated areas, allow overnight dry to sand and recoat). Allow 24 hours before hanging wallcovering when rolling adhesive on wall. Low temperature, high humidity, thick films or poor ventilation will increase these times.

**CLEAN-UP:** Clean immediately with warm, soapy water.

## P R E C A U T I O N S

**WARNING! CAUSES EYE, SKIN AND RESPIRATORY TRACT IRRITATION. MAY BE HARMFUL IF SWALLOWED. CONTAINS CRYSTALLINE SILICA WHICH CAN CAUSE LUNG CANCER AND OTHER LUNG DAMAGE IF INHALED. USE ONLY WITH ADEQUATE VENTILATION. KEEP OUT OF THE REACH OF CHILDREN.** For emergency information call (800)545-2643. If sanding is done, wear a dust mask to avoid breathing of sanding dust. Do not breathe vapors or spray mist. If you experience eye watering, headaches, or dizziness, leave the area. If properly used, a respirator may offer additional protection. Obtain professional advice before using. Close container after each use.

**FIRST AID:** In case of skin contact, wash off **quickly** with plenty of soap and water, remove contaminated clothing. For eye contact flush **immediately** with large amounts of water, for at least 15 minutes. **Obtain emergency medical treatment.** If swallowed, **obtain medical treatment immediately.** If inhalation causes physical discomfort, remove to fresh air. If discomfort persists or any breathing difficulty occurs, **get medical help.**

**KEEP FROM FREEZING!**

**Note: These warnings encompass the product series. Prior to use, read and follow product specific MSDS and label information.**

**DS6-0697**

ADSTOCK #78514

DR 51701

**LIMITATION OF LIABILITY:** To the best of our knowledge, the technical data contained herein are true and accurate at the date of issuance but are subject to change without prior notice. We guarantee our product to conform to the specifications contained herein. WE MAKE NO OTHER WARRANTY OR GUARANTEE OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING MERCHANTABILITY AND FITNESS FOR PARTICULAR PURPOSE. Liability, if any, is limited to replacement of the product or refund of the purchase price. LABOR OR COST OF LABOR AND OTHER CONSEQUENTIAL DAMAGES ARE HEREBY EXCLUDED.

**When It's Worth Doing Right!®**



**DEVOE PAINT**

925 Euclid Avenue  
Cleveland, Ohio 44115  
1-888-681-6353

Web Address: [www.devoepaint.com](http://www.devoepaint.com)