



Mid-Western States

PROMAR[®]

INTERIOR LATEX

**MOISTURE VAPOR BARRIER PRIMER/FINISH
B72WF210**

CHARACTERISTICS

ProMar Interior Latex Moisture Vapor Barrier Primer/Finish is a coating designed to reduce the loss of moisture through walls and ceilings. This product is designed for one coat application in manufactured housing facilities. Upon priming drywall or field installation of the home, this product can be topcoated with any Sherwin-Williams' interior latex or alkyd product.

Color: White
 Coverage: Recommended: 350 sq ft/gal @ 4.5 mils wet, 1.5 mils dry
 Drying Time @ 77°F 50% RH (temperature and humidity dependant)
 To touch: 30 minutes
 To topcoat: 1 hour
 Finish: 0-10 @ 85°
 Flash Point: 201°F, PMCC
 Perm Rating: less than 1.0 perms ASTM E96-A
 Solvent/Reducer: Water
 Tinting with Blend-A-Color:
 Base oz/gal Strength
 White 0-4 100%
 Vehicle Type: Styrene Butadiene
 VOC: 80 gr/L; 0.69 lb/gal
 Volume Solids: 30 ± 2%
 Weight Solids: 43 ± 2%
 Weight per Gallon: 10.2 lb

APPLICATION

Do not thin. Reduction will adversely affect the perm rating.
 Apply at temperatures above 50°F.

Brush - Use nylon/polyester brush
 Roller - Use 3/8" - 3/4" nap cover
 Spray - Airless
 Pressure 2000 psi
 Tip017"-.019"

SPECIFICATIONS

Drywall System 1:
 1-2 cts. ProMar Interior Latex Moisture Vapor Barrier Primer/Finish
 System 2:
 1 ct. ProMar Interior Latex Moisture Vapor Barrier Primer/Finish
 2 cts. Sherwin-Williams Interior, Latex or Alkyd, Architectural Topcoat

CLEANUP INFORMATION

Clean spills and spatters immediately with soap and warm water. Clean hands and tools immediately after use with soap and warm water. After cleaning, flush spray equipment with mineral spirits to prevent rusting of the equipment. Follow manufacturer's safety recommendations when using mineral spirits.

LABEL ANALYSIS

B72WF210

Pigment by Weight 27%
 Titanium Dioxide 10%
 Silica/Silicates 10%
 Calcium Carbonate 7%
 Vehicle by Weight 73%
 Styrene Butadiene Resin 12%
 Vinyl Acrylic Resin 2%
 Water 55%
 Additives 4%
 Total 100%

SURFACE PREPARATION

Remove all surface contamination by washing with ProClean All Surface Cleaner or other appropriate cleaner, rinse thoroughly and allow to dry. Existing peeled or checked paint should be scraped and sanded to a sound surface. Glossy surfaces should be sanded dull. Stains from water, smoke, ink, pencil, grease, etc. should be sealed with PrepRite ProBlock Primer Sealer.
Drywall
 Fill cracks and nail holes with patching paste/spackle and sand smooth. Joint compounds must be cured and sanded smooth. Remove all sanding dust.

CAUTIONS

Protect from freezing.

Non-photochemically reactive.

CAUTION contains CRYSTALLINE SILICA. Use only with adequate ventilation. To avoid overexposure, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air, or wear respiratory protection (NIOSH/MSHA TC23C or equivalent) or leave the area. Adequate ventilation required when sanding or abrading the dried film. If adequate ventilation cannot be provided wear an approved particulate respirator (NIOSH/MSHA TC21C or equivalent). Follow respirator manufacturer's directions for respirator use. Avoid contact with eyes and skin. Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage. **FIRST AID:** In case of eye contact, flush thoroughly with large amounts of water. Get medical attention if irritation persists. If swallowed, get medical attention immediately. **DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE.** Abrading or sanding of the dry film may release crystalline silica which has been shown to cause lung damage and cancer under long term exposure. **WARNING:** This product contains chemicals known to the State of California to cause cancer. **DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN.**

The information and recommendations set forth in this Product Data Sheet are based upon tests conducted by or on behalf of The Sherwin-Williams Company. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Sherwin-Williams representative to obtain the most recent Product Data Sheet.